

Pavigrés FilaSystem

A MANEIRA MAIS SEGURA PARA REMOVER AS MANCHAS THE SAFEST WAY TO REMOVE STAINS - LA FAÇON LA PLUS SÛRE D'ENLEVER LES TACHES DIE SICHERSTE ART DER FLECKENENTFERNUNG - EL MODO MAS SEGURO PARA ELIMINAR LAS MANCHAS	
TIPO DE MANCHA TYPE OF STAIN - TYPE DE TÂCHE- ART DER FLECKEN - TIPO DE MANCHA	GRÉS PORCELÂNICO PORCELAIN STONEWARE - GRÉS CÉRAME - FEINSTEINZEUG - GRES PORCELÂNICO
ÓLEO E GORDURA / OIL AND GREASE/ HUILE ET GRAISSE / ÖL UND FETT / ACEITE Y GRASA	FILA PS/87
PASTILHA ELÁSTICA / CHEWING GUM/ CHEWING-GUM / KAUGUMMI / GOMA DE MASCAR	FILA PS/87
CERVEJA / BEER /BIÈRE / BIER /CERVEZA	FILA PS/87
CAFÉ / COFFEE / CAFÉ / KAFFEE / CAFÉ	FILA SR/95 FILA PS/87
VINHO / WINE / VIN / WEIN /VINO	FILA SR/95 FILA PS/87
COCA COLA	FILA SR/95 FILA PS/87
VERNIZ / PAINT/ PEINTURE / LACK / PINTURA	FILA PS/87 FILA NOPAINT STAR
FERRUGEM / RUST/ ROUILLE / ROST/ HERRUMBRE	DETERDEK
CIMENTO - SALITRE / CEMENT- SALTPETRE / CIMENT - SALPÊTRE / ZEMENT - SALPETER / CEMENTO - SALITRE	DETERDEK
CALCÁRIO / LIMESCALE / CALCAIRE / KALK / CALIZA	DETERDEK
BETUME / TAR / BITUME / BITUMEN / ALQUITRAN	FILASOLV
CERA DEVELA / CANDLEWAX / CIRE DE BOUGIE / KERZENWACHS / CERA DEVELA	FILASOLV
COLA / GLUE / COLLE / KLEBSTOFF / ADHESIVO	FILA PS/87
PNEU / TYRE MARKS / TRACES DE PNEUS / REIFENSPUREN / NEUMATICO	FILA PS/87
TINTA / INK / ENCRE / TINTE / TINTA	FILA SR/95 FILA PS/87
NICOTINA / NICOTINE / NICOTINE / NIKOTIN / NICOTINA	FILA SR/95 FILA PS/87
GRAFITES /GRAFFITI / GRAFFITI / GRAFFITI / GRAFITOS	FILA NOPAINT STAR
JUNTA SUJA / DIRTY JOINT/ JOINT SALE / SCHMUTZIGE FUGEN / JUNTA SUCIA	FUGANET
CANETA / MARKER PEN / FEUTRE / FILZSTIFT / ROTULADOR	FILA SR/95 FILA PS/87
SINAIS METÁLICOS / METAL MARKS / TRACES MÉTALLIQUES / METALLSPUREN / MARCAS METÁLICAS	DETERDEK
TINTURA PARA CABELOS / HAIR DYE / TEINTURE POUR CHEVEUX / HAARFÄRBEMITTEL TINTE PARA CABELLOS	FILA SR/95 FILA PS/87
RESÍDUOS DE FITA ADESIVA / ADHESIVE TAPE MARKS / TRACES DE PAPIER COLLANT RÜCKSTÄNDE VON KLEBESTREIFEN / RESIDUOS DE CINTA ADHESIVA	FILASOLV FILA PS/87

www.filachim.com

Fila Industria Chimica Spa - Via Garibaldi 32
35018 San Martino di Lupari (PD) Italy
Tel. +39 049.9467300 - Fax 39 049.9460753 - info@filachim.com

Fila Chemicals Usa, Corp. - Tel. +1-305-513-0708 - filausa@filachim.com
Fila Deutschland Vertriebs GmbH - Tel. +49 (0)211.201016 - filadeutschland@filachim.com
Fila España Industria Química, S.L. - Tel. +34 964.590101 - filaespana@filachim.com
Fila France S.a.r.l. - Tel. +33(0)4.72.46.01.74 - filafrance@filachim.com

www.pavigres.pt

Pavigrés cerâmicas, s.a. - Apartado 42
3781-909 ANADIA - PORTUGAL
Tel: (+351) 231 510 600
Fax: (+351) 231 504 143
comercial@pavigres.com
export@pavigres.com

Washing after laying

Deterdek



Coverage:
40 m²
430 sq ft
dilution 1:5

- Sweep the floor well.
- Spread **Deterdek** diluted 1:5.
- Wait a few minutes.
- Pass with a floor cleaning machine with green disc and liquid vacuum cleaner or with a scrubbing brush and cloth.
- Rinse thoroughly.



Protecting the polished type

Fila MP/90



Coverage:
40 m²
430 sq ft
pure

- Apply pure **Fila MP/90** when the floor is dry (at least 4 hours after washing) using a flat brush, fleece, roller or cloth.
- When the floor is dry, remove the excess remaining on the surface using a floor cleaning machine with beige disc, with a clean cloth or with a floor polisher.
- Remove any remaining residues with a cloth moistened slightly with **FilaSolv**.



Maintenance

FilaCleaner



Coverage:
2000 m²
21000 sq ft
no rinsing

- Dilute **FilaCleaner** depending on the dirt.
No rinsing is required when it is highly diluted (1:200 – 25 ml in 5L / 1 fl oz in 1.3 gal water).
It can also be used in floor washing and drying machines at dilutions above 1:200).



Extraordinary intervention

Fila PS/87



Dilute **Fila PS/87**, spread and rinse.

Tenacious dirt	dilute 1:10
Remove old layers of Filajet	dilute 1:5
Remove the stains and residues of epoxy grout	pure

Impossible stains

Fila PS/87

Fila PS/87 eliminates all traces of coffee, wine, soft drinks, ink, felt-tip pen, shampoo... It does not attack the surface and the treatment if the floor has been protected with **Fila MP/90**. Any remaining halos can be removed using **Fila SR/95**.

- Pour pure **FilaPS/87** onto the stain.
- Leave to act for a few hours until it dries.
- Remove the residue with a moist sponge.
- The tile will be perfect again.

