

DECLARATION OF PERFORMANCE

N.º 001DDPMP

- 1. Unique identification code of the product type: Dry-pressed ceramic tiles, with water absorption greater than 10 % (Eb > 10 %), GL
- 2. Intended uses: For internal walls

Utilização: Revestimento de paredes interiores

- 3. Name and contact adress of the manufacturer: Pavigrés Cerâmicas, S.A., Almas das Domingas, 3781-909 Anadia, Portugal
- 4. System of assessment and verification of constancy of performance: System 4
- 5.Declared performances

Essential characteristics	Performance	Harmonised standard
Reaction to fire	A1	
Release of dangerous substances, for		
(1): - Cadmium (Cd) - Lead (Pb)	NPD	This 1441 2006
Breaking strenght (S)	≥ 300 N	EN 14411:2006
Durability: - Internal use:	Pass	
Tactility (2)	NPD	
Bond strenght / adhesion	NPD	-1 de america tilog ara usad

⁽¹⁾ Only for uses subject to regulation requirements on dangerous substances, i.e. when glazed ceramic tiles are used on surfaces in contact with food; to assess case by case.

NPD - No performance declared

The performance of the product identified in point 1 is in conformity with the declared performances in point 5.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

The Administrator

(José Diogo)

Anadia, 17/06/2013

⁽²⁾ For tactile paving surfaces only, i.e. when required for blind or vision impaired persons.