

DECLARATION OF PERFORMANCE

N.º 001DPPGP

1. Unique identification code of the product type: Dry-pressed ceramic tiles, with water absorption under, or equal to, 0.5% ($E_b \leq 0.5\%$), UGL or GL
2. Intended uses: For internal and external walls and floorings
3. Name and contact address of the manufacturer: Pavigrés Cerâmicas, S.A., Alto das Domingas, 3781-909 Anadia - Portugal
4. System of assessment and verification of constancy of performance: System 4
5. Declared performances

| Essential characteristics | Performance | Harmonised standard |
|--|-----------------------------|---------------------|
| Reaction to fire | A1 / A1FL | BS EN 14411:2012 |
| Release of dangerous substances, for (1): - Cadmium (Cd) - Lead (Pb) | NPD | |
| Breaking strength (S) | ≥ 1500 N | |
| Modulus of rupture (R) | ≥ 40 N/mm ² | |
| Slipperiness (2) | NPD | |
| Durability: - Internal use: - Freeze-thaw resistance: | Resistant | |
| Tactility (3) | NPD | |
| Bond strength / adhesion | NPD | |
| Thermal shock resistance | Resistant | |

(1) Only for uses subject to regulation requirements on dangerous substances, i.e. when glazed ceramic tiles are used on surfaces in contact with food; to assess case by case.

(2) For floorings on pedestrian circulation areas (where required by regulation).

(3) For tactile paving surfaces only, i.e. when required for blind or vision impaired persons.


NPD – No performance declared

The performance of the product identified in point 1 is in conformity with the declared performances in point 5.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

The President of the Board of Directors


(José Diogo)

Anadia, 07/05/2021